



Quality Architectural Hardware  
for Doors, Windows & Skylights

## FFI Multipoint Locks for Doors

*one handle activates multiple lock points*

Functional Fenestration Inc (FFI) has European Multipoint Door Locks that are well-suited to meet architectural demands for large openings, and designed to help meet performance requirements for secure alignment, warp-prevention and hurricane testing.



door with multipoint  
by Cascade Woodwork  
[www.cascadewoodwork.com](http://www.cascadewoodwork.com)

- **applications** – for wood, PVC, wood/aluminum or composite sashes
- **multipoints help prevent warping** – even for very tall sashes
- **shootbolts** – are included; optional non-shootbolt terminals are available
- **adjustable locking cams** – and non-cam options are available
- **mushroom cams** – optional upgrade for extra strength in testing
- **variable handle height** – cut the lock bottom and/or add extensions
- **cold-forged steel** – for extra strength, only from AGB
- **silver finish** – tested to 1,000 hours corrosion-resistance
- **standard milling groove** – 16mm Eurogroove is same for many brands

### Door multipoints – (see FFI catalog pages E-1 to E-12)

- for standard door heights (80", 96") and up to 12 foot tall doors.
- up to seven locking points; many configurations possible.
- AGB door multipoints are available in many backsets, from 25 mm to 55 mm.
- non-handed latch is easily reversible.
- Unitop multipoints are popular for patio door pairs.
- Poseidon hook multipoints are for sliding or single swing doors.



Unitop  
door lock



Poseidon  
door lock

### Accessories for multipoint

FFI Design has many products contract-manufactured exclusively for FFI. Many accessories are compatible with AGB, G-U, Hoppe, Winkhaus and other door and window multipoints.

- **door handles** with 8 mm square spindle and 92 mm center (J-DOR-1).
- **flush latch strikes** for American doors in satin nickel and oil-rubbed bronze (E-14).
- **thimble strikes** for shootbolts, in brass or silver, many sizes (E-12).
- **cylinders:** re-keyable, tang cylinders, satin nickel, ORB  
... thousands in-stock (E-18 to E-22).



strikes



cylinders



### Multipoint recommendations and tips

- Change handle height by cutting lock bottom and/or adding extensions.
- Locking cams can be removed simply by cutting them off, if cams are not wanted.
- The 16mm x 12mm hardware groove is the standard "Eurogroove"; in fact, locks, accessories and handles from many European multipoint brands are inter-compatible.

Contact FFI Customer Service for more information: 800-677-0228 or [service@fenestration.net](mailto:service@fenestration.net)